



Renco Electronics, Inc.

595 International Place Rockledge, Florida 32955

Tel: (321) 637-1000 | Fax: (321) 637-1600



Inductor Design Form

Company: _____

Contact: _____

Addr. 1: _____

Addr. 2: _____

City, State, Zip: _____

Telephone: _____ Fax: _____

Email: _____

Application: _____

Customer P/N: _____

Prototype Date: _____ Production Date: _____

EAU: _____ Project Name: _____

Target Price: _____ Submitted By: _____ Date: _____

Topology: Half-Bridge Buck Boost Buck-Boost
Full-Bridge Forward Push-Pull Other: _____

Shielding: Shielded Unshielded

Preferred Mounting Configuration: Surface Mount Leaded Axial Radial
Vertical Horizontal Toroid

Operating Frequency (kHz): _____ **Inductance (L):** _____ (uH, mH, H) **Waveform:** _____

Peak Current (Amps): _____ **RMS Current (Amps):** _____ **Peak-to-Peak Ripple Current:** _____

Ambient Temperature (°C): _____ **Max Operating Temperature (°C):** _____

Mechanical Information

Length (Max): _____ **Width (Max):** _____ **Height (Max):** _____

Optional Information

DC Resistance (Max): _____ (Ohms) **Q Factor (Min):** _____ **SRF (Min):** _____

Are there any other magnetics used in this design?

Switchmode Xfmr Current Sense Power Xfmr Common Mode

Notes

